

GT-500

5" Rugged Android™ Handheld Device with LTE solution



Features

- Support Android 5.1
- Quad-core ARM Cortex-A53 1.3GHz
- Multiple Connectivity including WLAN, WWAN, Bluetooth, NFC and 2G/3G/LTE.
- WorldMode modem capability (Support FDD/TDD-LTE, WCDMA, CDMA2000 1xEV-DO and GSM/GPRS/EDGE)
- IP67 rated water and dust resistance.
- Drop proof: Up to 1.5m
- Accelerometer, Magnetometer, Gyroscope, Light sensor, GPS & Barometer
- Built-in 1D barcode reader or 1D/2D barcode reader



System

CPU	Quad Core ARM Cortex-A53 1.3GHz
Operating System	Android 5.1
Memory	2GB LPDDR2
Flash	16 GB eMMC

Peripherals and Devices

Camera	Front: 2.0 megapixel camera Rear: 13.0 megapixel camera with Auto-Focus and Flashlight
Sensor	Magnetometer (M-Sensor/E-Compass)
	Accelerometer (G-sensor)
	Gyroscope
	Barometer
	Proximity sensor
Barcode Scanner	Ambient light sensor
	1D or 1D/2D barcode reader, either with physical trigger button
Audio & Vibrator	1 x built-in microphone 1 x built-in speaker (1W) 1 x 3.5mm stereo headphone/microphone combo jack 1 x vibrator FM radio

Wireless

WLAN	Integrated IEEE 802.11a/b/g/n
Bluetooth	Bluetooth 4.1 (BLE, HS compliant)
WWAN	2G GSM/GPRS/EDGE (Band 850 / 900 / 1800 / 1900) 3G WCDMA (Band 1,2,5,8) 3G CDMA2000 (BC0/BC1) 4G FDD+TDD (Band1,3,5,7,8,20,38,39,40,41) 4G DRX(Band1,3,5,7,8,20,38,39,40,41)
GPS	GPS/GLONASS/Beidou
NFC	Yes

I/O Interface

USB Port	1 x micro USB 2.0 port High Speed / OTG Compatible.
SD Slot	1 x microSD card slot
SIM card	1 x micro-SIM (3FF) socket supporting 2G/3G/LTE 1 x micro-SIM (3FF) socket supporting 2G only

LCD Display

Size/Type	5" TFT LCD
Resolution	720(W) x 1280(H)
Brightness (cd/m ²)	400 cd/m ²
Touch Screen	5 points capacitive touch (PCT)

Power Supply


Battery Type	Lithium-ion rechargeable battery, field replaceable.
Battery Capacity	Typical 3.7V, 4500mAh (TBD)
Adapter Input	AC 100~240V 50~60 Hz
Adapter Output	5V/2A (10W)

Mechanical & Environmental

Ingress Protection	IP67, Up to 1.5m drop resistance.
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	5% ~ 95% RH
Dimensions(mm)	165.8(H) x 85(W) x 23.1(D)
Weight	under 385g (with battery)



Dimensions



Ordering Information

Part Name	Description
GT-500-E	5" display, 720x1280 HD resolution, Quad-core 1.3 GHz CPU, Android 5.1, WiFi IEEE 802.11 a/b/g/n, BT4.1 BLE, NFC, WWAN 2G/3G/4G LTE, GPS, 1 x micro USB 2.0 port High Speed / OTG Compatible, 1 x microSD card slot, Dual SIM, RoHS, 2 + 13 Mega-pixel camera, IP67, Up to 1.5m drop resistance.
GT-500-A	5" display, 720x1280 HD resolution, Quad-core 1.3 GHz CPU, Android 5.1, WiFi IEEE 802.11 a/b/g/n, BT4.1 BLE, NFC, WWAN 2G/3G/4G LTE, GPS, 1 x micro USB 2.0 port High Speed / OTG Compatible, 1 x microSD card slot, Dual SIM, RoHS, 2 + 13 Mega-pixel camera, IP67, Up to 1.5m drop resistance, 2D barcode scanner

Packing Information

Part Name	Item	Description	Q'ty
GT-500-E	Rechargeable Li-ion battery pack	Typical 3.7V, 4500mAh	1
	Micro USB Cable		1
GT-500-A	QSG	Quick Start Guide	1

Optional Accessories list

Part Name	Description	Part Name	Description
Universal Power Adapter	5V/2A	4-in-1 Battery Charger	
Hand Strap		Desktop Cradle	

Functions Support Comparison

Part Name	Barcode	Bluetooth	Wi-Fi	GPS	3G	LTE	NFC	Camera
GT-500-E		V	V	V	V	V	V	V
GT-500-A	V	V	V	V	V	V	V	V

Solutions

Part Name	Retail	Transportation & Logistics	Warehouse	Medical	Energy	Manufacturing	Oil & Gas
GT-500-E	V	V		V		V	
GT-500-A	V	V	V	V	V	V	V

