



SPECIFICATION

MODEL	LK-B20(LK-B21)	LK-B230	
PRINTING METHOD	Thermal Transfer and Direct Thermal		
PRINTING SPEED (max)	152mm/sec	102mm/sec	
PRINT WIDTH (max)	104mm(4.1")		
PRINT LENGTH	1250mm(49.2")	650mm (25.5")	
RESOLUTION	203DPI(8 dots/mm)		
PAPER WIDTH (min~max)	18mm ~ 118mm(0.7" ~ 4.64")		
PAPER ROLL SIZE (min~max)	Internal : Ø 25.4(1") ~ Ø 127mm(5.0") External : Ø 38.1(1.5") ~ Ø 200mm(7.8")		
PAPER THICKNESS	0.06mm ~ 0.20mm		
PAPER TYPE	Label, Tag, Continuous, Fanfold		
PAPER SENSOR	Label Gap Sensor, Notch Sensor, Black Mark Sensor		
INTERFACE	STANDARD	USB, Parallel(IEEE-1284)	
	OPTION	Serial(RS-232C), Ethernet	
RIBBON WIDTH	33mm ~ 110mm(1.3 ~ 4.3")		
RIBBON LENGTH	360M, Ø 67mm(2.5")		
MEMORY	STANDARD	8MB SDRAM, 5MB Flash	
	OPTION	16MB Flash	
BARCODE	1D	Code39, Code128 with subsets A/B/C, Code93, Codabar, Interleaved 2 of 5, UPC-A and UPC-E with 2 or 5 digit extensions, EAN-8 and EAN-13 with 2 or 5 digit extensions, Postnet, Plessey, German Post Code, MSI-3, UCC/EAN-128	
	2D	Aztec Code, PDF 417, QR Code, DataMatrix, MaxiCode (EPL II and ZPL II), Code 49 (ZPL II)	Aztec Code, PDF 417, QR Code, DataMatrix, Code 49 (ZPL II)
FONT SPECIFICATION	6 bitmapped - 8x12, 10x16, 12x20, 14x24, 32x48, 24x24(KSC5601) 7 bitmapped - 5x9, 7x11, 10x18, 15x28, 13x26, 40x60, 13x21 1 smooth scalable	7 bitmapped - 5x9, 7x11, 10x18, 15x28, 13x26, 40x60, 13x21 1 smooth scalable	
DRIVER	Windows Printer Driver(2000, XP, 2003, 2008, Vista, 7 (32 & 64 bit), Linux Printer Driver		
POWER	AC 100~240V, 24VDC, 2.5A		AC 100~240V, 24VDC, 2.92A
DIMENSIONS	215mm x 287mm x 231mm		
WEIGHT(KG)	3.6KG		

DESKTOP BARCODE LABEL PRINTER LK-B20/B230

- Thermal transfer and Direct thermal printing
- Stable and reliable label printing
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Wax/Resin, Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional auto cutter or peeler



◀INTERFACE
Standard interface card
- USB
- Parallel(IEEE-1284)
Optional interface card
- Serial(RS-232C), Ethernet



◀Peeler



◀Auto cutter

APPLICATION

