



Intermec

## Product Profile



- Compact desktop printer for applications where space is limited
- **Connect & Print™** for easy setup – everything needed to get started printing immediately
- Unique double clam shell design offers easy drop-in loading of paper and ribbon supplies
- Serial and Centronics parallel interfaces are standard
- Optional EasyLAN Ethernet, IBM Twinax or Coax interfaces
- QuickMount™ printhead
- Free printhead replacement program
- Print speeds up to 4 inches per second
- Fully compatible with EasyCoder 7421 printer

### EASYCODER® PC41

Intermec's EasyCoder PC41 printer facilitates label printing in almost any environment including retail, office, healthcare, logistics, government, manufacturing, and warehouse – particularly where space is limited. The PC41 is a small, compact desktop printer that prints labels, tickets, and tags up to 4.1 inches wide to meet compliance mandates.

Connect & Print features of the EasyCoder PC41 printer ensure quick and easy setup and printing. The PC41 printer comes standard with software, drivers, cables, labels, and QuickStart Guide to facilitate getting started. Businesses can integrate the PC41 bar code label printer with minimal training efforts.

The unique double clam shell design minimizes down time with quick and easy media replenishment and QuickMount™ printhead changes. Labels and ribbons are easily swapped out via drop-in replacement. Additionally, Intermec offers a free printhead replacement program for customers who utilize Intermec printer supplies with the EasyCoder bar code label printer.

Flexible communication options enable users to utilize open ports without interfering with equipment that may already be connected to the computer. The EasyCoder PC41 comes standard with RS-232 Serial and Centronics parallel interfaces. Optional interfaces include external EasyLAN™ Ethernet or IBM Twinax or Coax interfaces.

The EasyCoder PC41 printer is backwards compatible with existing EasyCoder 7421 printer installations. These small desktop label printers utilize Intermec's unique programming language IPL. They are frequently used in conjunction with larger label printers such as the EasyCoder 3400e, 4420, and 4440 printers.

Bar code label printing has never been so easy. The EasyCoder PC41 facilitates getting started with Connect & Print features, choice of stationary or mobile printing, and quick and easy media replenishment in a small compact printer designed to fit where space is limited.

Intermec

**Application**

Direct Thermal or Direct Thermal / Thermal Transfer label, ticket, and tag printer.

**Physical Characteristics**

**Length:** 257 mm (10.11 in)

**Height:** 167 mm (6.58 in)

**Width:** 230 mm (9.06 in)

**Weight:** 2.3 kg (5.07 lbs)

**Print Specifications**

**Max Print Width:** 108 mm (4.25")

**Print Speed**

Selectable 2, 3, and 4 ips (50.8, 76.2, and 101.6 mm/sec)

**Print Resolution**

8 dots/mm (203 dpi)

**Label/Ticket/Tag**

**Max Width:** 118 mm (4.65 in)

**Min. Width:** 25 mm (1 in)

**Thickness (includes liner):** 0.06 mm (0.003 in) to 0.15 mm (0.006 in)

Optional thick media spring for media up to 0.20 mm (0.008 in)

**Style:** Roll-fed, die-cut, continuous or fanfold labels, tags or tickets

**Label roll max diameter:** 127 mm (5 in)

**Label roll core ID (min/max):** 25.4 mm (1 in) / 38.1 mm (1.5 in)

**Media type:** Thermally sensitive media

**Ribbon Roll**

**Ribbon roll max diameter:** 41 mm (1.6 in)

**Ribbon roll core inner diameter:** 13 mm (0.5 in) with notches

**Ribbon type:** Wax, wax/resin, resin

**Interface**

**Standard:** RS-232 Serial and Centronics Parallel

**Optional:** External Ethernet, IBM Twinax or Coax

**Connect & Print**

Printer comes standard with software, drivers, cables, labels, and QuickStart Guide to facilitate getting started.

**Software**

LabelShop® START label design software InterDriver™ with ActiveX® Controls for Microsoft® Windows™

**Bar Code Symbolologies**

1-D: Code 11, Code 39, Extended Code 39, Code 93, Extended Code 93, Code 128 UCC, Code 128, Codabar, Interleaved 2 of 5 UPC-A, UPC-E, 2 and 5 digit add-on, UPC Shipping container code, EAN-13, EAN-8, 2 and 5 digit add-on, EAN-128, Postnet  
2-D: Code One, Code 16K, Code 49, Data-Matrix, MaxiCode, PDF417, QR Code

**Fonts**

Supports 21 resident bitmap, 3 resident scalable fonts, and users can download up to 16 bitmap fonts using PrintSet™.

**Character Sets**

**Resident codepages:** Code page 850, French, German, ISO 256 character, Italian, Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII.

**Memory**

**Standard:** 512 kB RAM

**Optional:** 1 MB Flash

**Protocol**

IPL (Intermec Programming Language)

**Power Supply**

Separate power supply unit –

**Input:** 100-240V AC/50-60 Hz, 1.9A

**Output:** 24 V DC, 3.0 A

**Operating Environment**

**Operating temperature:** 5°C to 40°C (40°F to 104°F)

**Storage temperature:** -20°C to 60°C (-4°F to 140°F)

**Humidity:** 10% to 90% non-condensing

**Regulatory Approvals**

FCC 47 CFR part 15A, CE, UL + cUL, GS, NOM, C-Tic

**Options**

Cutter, 1 MB Flash Memory Cartridge, EasyLAN External Ethernet Adapter, IBM Twinax or Coax Interfaces

**Intermec®**  
e x p e c t **MORE®**

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

**Systems & Solutions**

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**

9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Canada**

7065 Tranmere Drive  
Mississauga, Ontario  
L5S 1M2 Canada  
tel: 905.673.9333  
fax: 905.673.3974

**Europe/  
Middle East & Africa**

**Headquarters**  
Sovereign House  
Vastern Road  
Reading RG1 8BT  
United Kingdom  
tel: 44.118.987.9400  
fax: 44.118.987.9401

**Asia**

**Asia Regional Office**  
26-16 International Plaza  
10 Anson Road  
Singapore 079903  
tel: 65.6324.8391  
fax: 65.6324.8393

**Beijing Representative Office**

29 FL, Unit A1, China Merchant Tower  
118 Jian Guo Road  
Chaoyang District, Beijing 100022  
Tel: 86 10.5165.5922  
Fax: 86 10.6567.6778

**Australia**

Level 7, 200 Pacific Highway  
Crows Nest, NSW 2065  
Australia  
tel: 61.2.9492.4400  
fax: 61.2.9954.6300

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Samuel Morse 120 9 andar  
Brooklin CEP04576-060  
São Paulo, SP  
Brazil  
tel: 55.11.5502.6770

**Intermec Technologies de Mexico**

Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa  
Mexico, DF, 06140 Mexico  
tel: 525.55.211.1919  
fax: 525.55.211.8121

**Internet**

www.intermec.com

**Sales**

800.347.2636  
(toll free in N.A.)  
tel: 425.348.2726

**Service and Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.  
611586-01A 01/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.