



● SPECIFICATION

MODEL	LK-B10(LK-B11)	LK-B12	
PRINTING METHOD	Thermal Transfer and Direct Thermal		
PRINTING SPEED (max)	102mm/sec	127mm/sec	
PRINT WIDTH (max)	104mm(4.1")		
PRINT LENGTH	630mm(24.8")		
RESOLUTION	203DPI(8 dots/mm)		
PAPER WIDTH (min~max)	18mm ~ 118mm(0.7"~ 4.64")		
PAPER ROLL SIZE (min~max)	Internal : Ø 25.4(1") ~ Ø 127mm(5.0") External : Ø 38.1(1.5") ~ Ø 200mm(7.8")		
PAPER THICKNESS	0.06mm ~ 0.20mm		
PAPER TYPE	Label, Tag, Continuous, Fanfold		
PAPER SENSOR	Label Gap Sensor, Notch Sensor, Black Mark Sensor		
INTERFACE	STANDARD	Serial, parallel	Built in USB & Parallel (optional) on board
	OPTION	USB, Ethernet	
RIBBON WIDTH	33mm ~ 110mm(1.3 ~ 4.3")		
RIBBON LENGTH	360M, Ø 67mm(2.5")		
MEMORY	STANDARD	8MB SDRAM, 3.5MB Flash	8MB SDRAM, 3MB Flash
	OPTION	4MB Flash	4MB Flash
BARCODE	1D	Code39, Code128 with subsets A/B/C, Code 93, Codabar, Interleaved 2 of 5, UPC-A and UPC-E With 2 or 5 digit extensions, Postnet, Plessy, German Post Code, MSI-3, UCC/EAN-128	
	2D	PDF417, MaxiCode, QR Code (EPL II)	
FONT SPECIFICATION	6 bitmapped - 8x12, 10x16, 12x20, 14x24, 32x48, 24x24(KSC5601)		
PROGRAMMING LANGUAGE	EPL II Command compatible		
POWER	AC 100~240V, 24VDC, 2.5A		
DIMENSIONS	215mm x 287mm x 231mm		
WEIGHT(KG)	3.6KG		

DESKTOP BARCODE LABEL PRINTER

LK-B10/B12

- Thermal transfer and Direct thermal printing
- Stable and reliable label printing
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Wax/Resin, Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional auto cutter or peeler (LK-B10)



◀ LK-B10 INTERFACE
Standard interface card
- Serial(RS-232C)
- Parallel(IEEE-1284)
Optional interface card
- USB, Ethernet



◀ LK-B10 Peeler



◀ LK-B12 INTERFACE
Standard interface card
- USB
- Parallel(IEEE-1284)



◀ LK-B10 Auto cutter

● APPLICATION

