

RFID HANDHELD READERS

Real-Time Mobile Computing with RFID Delivers Real Business Value

The MC9000-G RFID from Symbol Technologies is a ruggedized mobile computer that features integrated support for the most popular radio frequency identification standard — EPC™, the Electronic Product Code. By integrating support for EPC Generation 1 (Gen 1) and Generation 2 (Gen 2) -Ready with a firmware upgrade, RFID reading and programming with a robust commercial mobile computer, the MC9000-G is able to offer an extraordinary level of functionality suitable for a broad range of RFID applications. Combining RFID, bar code reading, imaging, 802.11 connectivity, a full 1/4 VGA screen and alphanumeric keypad, the MC9000-G RFID has the flexibility to give your organization real-time access to mission-critical information from key points in your supply chain. Enterprise-wide management and control of the MC9000-G is easy with Symbol's Mobility Services Platform (MSP).

Many of the world's largest retailers, manufacturers and logistics organizations are integrating RFID as part of their supply chain processes, and RFID is rapidly emerging as a key technology across a wide range of markets and applications. With a feature set that delivers exceptional data collection, communication and collaboration, the MC9000-G RFID facilitates faster decision-making and increased productivity in a variety of environments — from the factory to the warehouse to the sales floor.

Mobile Solutions Add Value to RFID

Traditional supply chain applications of RFID rely on automatic reading of tagged items using fixed readers installed at dock doors, mechanized conveyors, depalletization stations and other "choke" points in the movement of goods. However, when integrated with a mobile solution, RFID technology expands and improves the general functionality and performance of your entire mobile application.

Services for a More Successful Mobility Solution

Symbol offers a full suite of services, including analysis, design, installation, training and ongoing support for the deployment, management and continued support of your RFID solution.

For more information on the MC9000-G RFID and its full line of accessories, contact us at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at www.symbol.com/mc9000grfid.



FEATURES

Supports EPC Class 0 Class 1 and Gen 2-Ready via firmware upgrade

Extremely rugged design withstands multiple 6 ft./1.8 m drops to concrete; 2,000 3.3 ft./1 m tumbles (4,000 hits)

Multi-modal: integrated bar code scanning, imaging and RFID

IP64 sealing rating (electronic enclosure)

Microsoft® Windows® CE .NET 4.2 & Windows Mobile 2003 operating systems

Intel® XScale™ PXA255 processor at 400 MHz

3.8 in. large, bright, color display with backlit keypad

Wireless LAN communications

Forward scanning, pistol grip ergonomics

Integrated directional antenna (70-degree forward-looking)

API (Application Programming Interface) for Microsoft® Windows® CE .NET 4.2 & Windows Mobile 2003

BENEFITS

Allows easy integration of RFID as part of your supply chain processes; ready for transition from Gen 1 to Gen 2

Ensures less down time due to accidental drops

Great flexibility for enterprise applications

Protects against water and dust to ensure reliable performance in rough conditions

Gives versatility through familiar interfaces with wide software application support

Delivers high-speed CPU performance for robust enterprise applications, including multimedia

Allows easy viewing in many environments, such as ambient light

Enables real-time data exchange for maximizing productivity

Reduces user fatigue in scan-intensive applications

Enables you to isolate the RFID tags you are interested in

Use familiar tools to build RFID-enabled applications

MC9000-G RFID Specification Highlights

Physical and Environmental Characteristics

Dimensions:	10.75 in. L x 4.7 in. W x 7.7 in. H 27.3 cm L x 11.9 cm W x 19.5 cm H
Weight:	35.4 oz./1 kg (includes battery, scanner and radio)
Keyboard:	53-key
Display:	Microsoft® Windows CE.NET 4.2 models: 3.8 in. 1/4 VGA Mono Microsoft® Windows Mobile models: 3.8 in. 1/4 VGA Mono or Color
Power:	Removable, rechargeable 7.4 volt 2200 mAh Li Ion battery pack (2200mAh, 7.4V)

Performance Characteristics

CPU:	XScale PXA255 processor at 400 MHz
Operating Systems:	Microsoft® Windows Embedded CE. NET 4.2 and Microsoft® Windows Mobile 2003
Memory RAM/ROM:	64/64 MB
Application Development:	SDK available through Symbol Developer Zone Web site
Bar Code Options:	Microsoft® Windows Mobile 2003 models: omnidirectional 1D and 2D imaging Microsoft® Windows CE.NET 4.2 models: omnidirectional 1D scanning

User Environment

Operating Temperature:	Monochrome/Color: -4° to 122° F/-20° to 50° C
Storage Temperature:	-25° to 160° F/-40° to 70° C
Humidity:	5% to 95% non condensing
Drop Spec:	Multiple drops to concrete: 6 ft/1.8 m: 14° C to 122° F/-10° C to 50° C 5 ft/1.5 m: -13° C to 14° F/-25° C to -10° C
Tumble:	2,000 3.3 ft./1 m tumbles at room temperature (4,000 hits)
Environmental Sealing:	IP64 (electronic enclosure)
ESD:	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

RFID

Standards supported:	EPC Gen 1 (Class 0 & Class 1) and Gen 2-Ready via firmware upgrade
Nominal read range*:	0.2 ft. to 10 ft./6.09 cm to 304.8 cm
Nominal write range*:	1 ft. to 2 ft./30.5 cm to 60.9 cm
Field:	70-degree cone (approx.) measured from nose of device
Antenna:	Integrated, linearly polarized
Frequency Range:	902-928 MHz
Output Power:	1W (4W EIRP)

Wireless Data Communications

WLAN:	802.11b
Output Power:	100 mW
Data Rate:	802.11b: 11 MB per second
Antenna:	Internal
Frequency Range:	Country-dependent; typically 2.4 to 2.5 GHz

Peripherals and Accessories

Cradles:	Single-slot and 4-slot cradles available
Printers:	Supports extensive line of Symbol-approved printers, cables and accessories
Charger:	4-Slot universal battery charger
Other Accessories:	Cable adapter module; snap-on magnetic stripe reader and modem; holster

Regulatory

General:	Suitable for sale in the United States and Canada only
Electrical Safety:	Certified to UL60950, CSA C22.2 No. 60950
EMI/RFI Radio Versions:	North America: FCC Part 2 (SAR), FCC Part 15 RSS210 Class B (Class 1 model only)
Laser Safety:	IEC Class2/FDA Class II in accordance with IEC60825-1/EN60825-1

*Actual read/write range is dependent upon a number of factors, including the specific tag used, nature of the items tagged and presence or absence of radio interference.

MC9000-G RFID: Market, Applications and Users

Market	Applications	User
Manufacturing	Inventory management Supply-line replenishment	Assembly-line personnel Shipping/receiving personnel
Retail	Warehouse management Price audits/changes Store receiving Inventory management	Sales associates Receiving-dock personnel Stock-room personnel Supervisors
Wholesale	Warehouse management Receiving/Putaway/Shipping	Warehouse personnel
Distribution	Returns processing	Loading-dock personnel
Third-party logistics	Warehouse management	Warehouse personnel
Pharmaceutical	Enhanced Traceability	Compliance personnel
Aviation	Parts Tracking Baggage	Maintenance personnel Baggage handling personnel
Defense	Logistics/Supply	Service personnel

How Do Mobile Solutions Add Value to RFID Technology?

Challenge	Mobile Solution Value
Exception Processing	Allows misreads and other problem shipments to be investigated away from the dock without impeding flow
Remote Location Support	Provides a means of utilizing RFID information for receiving — even in the middle of a desert
Quick Start	No installation and low total solution cost allows a "quick start" with RFID
In Situ Processing	Goods stored away from fixed readers — e.g., in storage racks — can still be processed using RFID tag information
Mixed Bar Code and RFID	Lets workers switch quickly between RFID-tagged items and items marked with a bar code

About Symbol Technologies

Symbol Technologies, Inc., The Enterprise Mobility Company™, is a recognized worldwide leader in enterprise mobility, delivering products and solutions that capture, move and manage information in real time to and from the point of business activity. Symbol enterprise mobility solutions integrate advanced data capture products, radio frequency identification technology, mobile computing platforms, wireless infrastructure, mobility software and world-class services programs under the Symbol Enterprise Mobility Services brand. Symbol enterprise mobility products and solutions are proven to increase workforce productivity, reduce operating costs, drive operational efficiencies and realize competitive advantages for the world's leading companies. More information is available at www.symbol.com.



Corporate Headquarters
Symbol Technologies, Inc.
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722-6234
+1.631.738.2400
FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
(Singapore Branch)
Asia Pacific Division
230 Victoria Street #12-06/10
Bugis Junction Office Tower
Singapore 188024
TEL: +65.6796.9600
FAX: +65.6337.6488

For Europe, Middle East and Africa
Symbol Technologies
EMEA Division
Symbol Place, Winners Triangle
Berkshire, England RG41 5TP
TEL: +44.118.9457000
FAX: +44.118.9457500

For North America, Latin America and Canada
Symbol Technologies
The Americas
One Symbol Plaza
Holtsville, NY 11742-1300
TEL: +1.800.722.6234
+1.631.738.2400
FAX: +1.631.738.5990

Symbol Website
For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com
E-mail
info@symbol.com



Part No. MC9000G-RFID Printed in USA 08/05 © Copyright 2005 Symbol Technologies, Inc. All rights reserved. Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply. Specifications are subject to change without notice. Symbol® is a registered trademark of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners. For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.

MC9000G-RFID 08/05